



PRODUCT FACT SHEET

STREAMLIGHT 2AA PROPOLYMER® XENON or LED ALKALINE BATTERY POWERED FLASHLIGHT

MARKET APPLICATIONS:	Industrial, Occupational Safety, Fire & Rescue, Sporting Goods, Law Enforcement, Security, Hardware/Tool, Consumer
DESCRIPTION:	The 2AA ProPolymer is an extremely durable, waterproof alkaline battery-powered flashlight. This light offers a push-button tailswitch for momentary and on-off operation.
CASE MATERIAL:	Housing made from high impact super tough nylon offering exceptional durability. Rubber coated facecap resistant to impact and shock.
DIMENSIONS:	Length: 6.30 in. (16.00 cm) Diameter: Major Diameter: 1.30 in. (3.30 cm) Body Diameter: 0.89 in. (2.26 cm)
WEIGHT:	3.6 oz (100 grams)*
LENS:	Unbreakable polycarbonate with scratch-resistant coating.
LIGHT SOURCE:	Xenon - Gas filled bi-pin bulb in parabolic reflector module. LED - One (1) 0.5 Watt High-Flux LED, 30,000 hour lifetime in parabolic reflector module.
LIGHT OUTPUT:	Xenon- Up to 4,500 Peak Beam candlepower. Bulb Rating: 9 lumens typical. LED Rating - 25 Lumens typical. Parabolic reflector produces a focused beam with optimum peripheral illumination.
ON/OFF:	Push button tail switch.
RUN TIME:	Xenon - Up to 4 hours continuous run. LED - 18 continuous hours at regulated intensity.
BATTERY:	(2) 1.5V "AA" alkaline cells - included in package.
FEATURES:	O-Ring sealed construction Dust and water ingress protected to IP57; in accordance with specification EN60529:1992 Impact resistant housing - drop test verified LED - Solid state power regulation provides maximum light output throughout battery life Push button tail switch for On/Of
APPROVALS**:	Most models meet applicable European Community Directives. CE <u>2AA Xenon - UL Listed</u> Class I, Div 1, Groups C, D Class I, Div 2, Groups A, B, C, D Class II, Div 2, Groups F, G Class III Temperature Code T3C <u>2AA Xenon - CUL Listed</u> Class I, Div 2, Groups A, B, C, D Class II, Div 2, Groups F, G Class III Temperature Code T3C
APPROVALS** Continued:	<u>2AA LED - UL Listed, CUL Listed</u> Class I, Div 2, Groups A, B, C, D Class II, Div 2, Groups F, G Class III Temperature Code T4
WARRANTY:	Limited lifetime warranty.
OPTIONAL ACCESSORIES:	N/A

* With battery (included in purchase)

** See product for specific ratings.

Assembled In The USA.