



PRODUCT DATA SHEET

Product: PM-2 Packaging Tape - Medium Strength

Description: A quick, sure sealing, economical, pressure-sensitive flatback tape which can increase packaging line efficiency. PM-2 offers a positive attractive seal and excellent adhesion to discourage pilfering. Performs well under a wide range of temperatures through a wide range of humidity conditions. Can be used on all types of cartons. Offers the advantages of a balance of high quick stick and excellent holding properties. Performs well as a low temperature splicing tape. Meets USPS requirements. Product is not repulpable.

Nominal Values:	Backing	Kraft Flatback
	Adhesive	Natural Rubber/Resin
	Adhesion to Steel (oz/in of width)	57 (15.6 N/25mm)
	Quick Stick (oz/in of width)	
	To Kraft	11 (3 N/25mm)
	To Steel	25 (6.8 N/25mm)
	Tensile Strength (lbs/in of width)	50 (219 N/25mm)
	Elongation (% at break)	3
	Thickness (mils)	6.0 (0.15 mm)
	Color	Tan
	Specification Conformance	ASTM D6123, Type II PPP-T-42C, Type II C.I.D. A-A-883B Type II

Features: Temperature resistant operating range of 40° F to 225° F. (4°C to 107°C)

Standard Sizes: 12mm x 54.8m, 18mm x 54.8m, 24mm x 54.8m, 36mm x 54.8m, 48mm x 54.8m, 72mm x 54.8m, and 96mm x 54.8m

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

02-08