

J-SYSTEM[®]

What is the J-System[®]?

The J-System[®] provides a precise and even air movement within a grain mass of any storage facility regardless of its size or shape. The J-System[®] blower's design is coordinated with the controlled release of hydrogen phosphide from Phostoxin[®], allowing a lethal concentration of the fumigant may be obtained throughout the grain mass in quality, tightly sealed storages.

How does the J-System[®] work?

Using the patented J-System[®] blower, air is drawn from the headspace and pushed into the grain mass through your aeration system, establishing a uniform hydrogen phosphide concentration. The dispersion of the fumigant gas concentration continues until all the fumigant has been liberated. Uniform gas concentrations in all areas of the grain mass assure high insect mortality.

The J-System[®] is economical to install externally or internally due to our blower's explosion resistant classification. Component parts can be custom designed and engineered for your storage facility, including ones without an existing aeration system. It is currently used on all types of grain storage facilities including corrugated steel tanks, steel welded or bolted tanks, concrete silos, flat houses, bunker storages, barges and ship holds.


J-System[®] Low Air Flow Fumigation Method



Bin A


Bin B

These bins, A & B, represent how a bin with nothing to help equalize the gas concentration may appear in 24 to 72 hours. Uneven distribution is apparent even if the bin is top and bottom treated as in B.



This represents how a bin with the J-System[®] will appear in relation to gas concentration in only 12 to 24 hours.

B9 Blower Specifications



CONSTRUCTION:

- CAST ALUMINUM HOUSING
- CAST ALUMINUM IMPELLER

IMPELLER:

- 8.8" DIAMETER 2.69" WIDE

INLET SIZE :

- 5.8"
- FREE AREA 23.4 SQ. INCHES

DISCHARGE SIZE:

- 3.8"
- FREE AREA 9.4 SQ. INCHES

THE BLOWER IS CONSTRUCTED TO AMCA TYPE C SPARK RESISTANT SPECIFICATION.

MOTOR SPECIFICATION:

- ½ HP
- 1 PHASE
- 60 Hz
- 115 / 230 VOLTS
- RPM - 3450

DUTY:

- CONTINUOUS @ 40°C AMBIENT
- FRAME 56C
- THERMALLY PROTECTED
- S.F. 1

UNDERWRITERS LABORATORY LISTED
CE APPROVED
CUL LISTED

EXPLOSION PROOF:

- CLASS I GROUP C, D
- CLASS II GROUP F, G

Performance of B9 Blower at 3450 RPM

